



Designed for dependable drainage

SWR DRAINAGE SYSTEMS



SWR DRAINAGE SYSTEMS

Spectra's SWR drainage systems are built for quick and effective removal of soil, waste and rainwater without leakage. It's highly resilient and durable feature gives a long service life. They are available in Solvent type and Ring type jointing system that is widely used in residential and commercial settings.



FEATURES & BENEFITS



Smooth Bore Ensures
Higher Flow



Excellent Chemical
& Corrosion Resistance



Long Life &
Maintenance Free



Cost Effective

Product Range

Pipes	75mm to 160mm
Fittings	75mm to 110mm

Standards

Pipes	IS 13592
Fittings	IS 14735

Applications

- Complete drainage and ventilation systems for buildings
- Rain water discharge & harvesting for residential, complexes & commercial spaces
- Industrial buildings
- Public utilities

Dimensions of SWR Drainage Systems

Pipes as per
IS : 13592



CM/L - 4451659

Fittings as per
IS : 14735



CM/L - 6200016683

Nominal Outside Diameter (D) in mm	Tolerance on Outside Diameter in mm	Wall Thickness Type-A (t) in mm		Wall Thickness Type-B (t) in mm	
		Min	Max	Min	Max
75	+0.3	1.8	2.2	3.2	3.8
90	+0.4	1.9	2.3	3.2	3.8
110	+0.4	2.2	2.7	3.2	3.8
160	+0.5	3.2	3.8	4.0	4.6

HEAD OFFICE